

Access Point U6+



Mechanical

Dimensions	Ø160 x 33 mm (Ø6.3 x 1.3")
Weight	Without mount: 338 g (0.75 lb) With mount: 413 g (0.91 lb)
Enclosure materials	Top cover: polycarbonate Bottom cover: aluminum
Mount materials	ABS, SGCC steel

Hardware

Networking interface	(1) GbE RJ45 port	
Management interface	Ethernet	
Power method	PoE	
Supported voltage range	44-57V DC	
Max. power consumption	9W	
Max. TX power	2.4 GHz	23 dBm
	5 GHz	23 dBm
MIMO	2.4 GHz	2 x 2
	5 GHz	2 x 2
Throughput rate	2.4 GHz	573.5 Mbps
	5 GHz	2402 Mbps
Antenna gain	2.4 GHz	3 dBi
	5 GHz	5.4 dBi
LED	White/blue	
Button	Factory reset	
Mounting	Wall/ceiling (included)	
Operating temperature	-30 to 60° C (-22 to 140° F)	
Operating humidity	5 to 95% noncondensing	
Certifications	CE, FCC, IC	

Software

WiFi standards	802.11a/b/g WiFi 4/WiFi 5/WiFi 6
Wireless security	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)
BSSID	8 per radio
VLAN	802.1Q
Advanced QoS	Per-user rate limiting
Guest traffic isolation	Supported
Zero wait DFS	Not supported
Concurrent clients	300+



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2022 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.